



Scotch® Box Sealing Tape 311+

Product Data Sheet

November 2019
Supersedes: NEW

Product Description

Scotch® Box Sealing Tape 311+ is an industrial packaging tape for box sealing, splicing and recoupage on light to medium weight boxes. The product offers good performance over broad temperature ranges; specifically, in colder and damper applications; and adheres to recycled fiber board

Key Features

- Adheres to a variety of surfaces
- Good aging in sunlight of fluorescent lighting
- Edge tear and split resistance
- Adheres well to recycled corrugate
- Conformable backing.

Performance Characteristics

| Box Sealing Tape 311+ | Test Method | Result |
|-----------------------|----------------|--------------|
| Thickness Total | ASTM D-3652-01 | 50 µm |
| Film Thickness | ASTM D-3652-01 | 28 µm |
| Tensile Strength | ASTM D-3759-05 | 393 N/100 mm |
| Elongation @ Fmax | ASTM D-3759-05 | 150 % |
| Adhesion to Steel | ASTM D-3330-4 | 27 N/100 mm |

Application Techniques

An extensive line of application equipment including handheld manual dispensers and semi-automatic and fully automatic equipment is available. Scotch® Box Sealing Tape 311+ has been applied to fibreboard boxes with good results at freezer and refrigeration temperatures of -6.6 °C to 10 °C. Once applied, Scotch® Tape 311+ performs well on fibreboard boxes subjected to temperatures below 0 °C .

Storage & Shelf Life

Store at 4 °C – 26 °C and 40-50 % relative humidity in its original box. The product can be stored up to 18 months after date of production.

Note: The shelf life may be shortened if the original packaging is not properly sealed or stored in an environment with high temperatures or humidity

For Additional Information

To request additional product information or to arrange for sales assistance, call.....
Address correspondence to:

Important Notice

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark the 3M Company.

| |
|---|
| <p>3M Poland Sp. z o.o. Closure and Masking Division Aleja Katowicka 117, Kajetany k/Warszawy 05-830 Nadarzyn tel.: (022) 739 60 00. www.3m.pl</p> |
|---|